

# INFLATING GUNS

Accurate and reliable, they have always been a measurement instrument selected and appreciated by the most demanding professionals and DIY lovers.

From the legendary PG/S to the brand new PG/PRO, the result of years of technical, functional and aesthetic research associated with decades of experience in this sector, the Asturomec® inflation gun range is the most complete and professional range on the market.

Precision instruments with top quality pressure gauges, equipped with FAIL SAFE GAUGE SAFETY VALVE that prevents gauge needle oscillations during use, cutting it off from the air line during inflation.

Available in the CEE/OM version, meeting EEC D96 18.08.02 nr. 71/316 directive standards for pressure gauges and gun (check First).



**PG PRO CEE/OM**

Ref. 50180/O

Professional inflating gun **EEC approved.**  
 Pressure-gauge protecting safety valve  
 Body: nickel-plated brass, Marfran C shockproof and nonslip grip  
 Lever: single pressure load made of stainless steel  
 Two-way release button: fast or regulation  
 PVS pressure reading system  
 Gauge: diam. 80 mm EEC approved-range 0-10 bar  
 Length of tube: 1 m

Operating air pressure: 1.0 - 6.0 bar  
 Package: 1 pcs  
 Weight: 910 g



Recommended use:



**PG/G PRO CEE/OM**

Ref. 50181/O

Professional inflating gun **EEC approved, for twin or spoked wheels.**  
 Pressure-gauge protecting safety valve  
 Brass inflating head, 30 cm long  
 Body: nickel-plated brass, Marfran C shockproof and nonslip grip  
 Lever: single pressure load made of stainless steel  
 Two-way release button: fast or regulation  
 PVS pressure reading system  
 Gauge: diam. 80 mm EEC approved-range 0-10 bar  
 Length of tube: 1 m

Operating air pressure: 1.0 - 6.0 bar  
 Package: 1 pcs  
 Weight: 1.02 Kg



Recommended use:



**PG PRO**

Ref. 50182

Professional inflating gun.  
 Pressure-gauge protecting safety valve  
 Body: nickel-plated brass, Marfran C shockproof and nonslip grip  
 Lever: single pressure load made of stainless steel  
 Two-way release button: fast or regulation  
 PVS pressure reading system  
 Gauge: diam. 80 mm - range 0-10 bar  
 Length of tube: 1 m

Operating air pressure: 1.0 - 6.0 bar  
 Package: 1 pcs  
 Weight: 800 g



**PG/G PRO**

Ref. 50183

Professional inflating gun, for twin or spoked wheels.  
 Pressure-gauge protecting safety valve  
 Brass inflating head, 30 cm long  
 Body: nickel-plated brass, Marfran C shockproof and nonslip grip  
 Lever: single pressure load made of stainless steel  
 Two-way release button: fast or regulation  
 PVS pressure reading system  
 Gauge: diam. 80 mm - range 0-10 bar  
 Length of tube: 1 m

Operating air pressure: 1.0 - 6.0 bar  
 Package: 1 pcs  
 Weight: 930 g



Recommended use:



**PG/S CEE/OM**

Ref. 50108/O

Inflating gun **EEC approved.**  
 Pressure-gauge protecting safety valve  
 Body: nylon  
 Lever: single operation with double acting pressing filling and release lever  
 Gauge: diam 63 mm EEC approved-range 0-10 bar  
 Length of tube: 80 cm

Operating air pressure: 1.0 - 6.0 bar  
 Package: 1 pcs  
 Weight: 460 g



Recommended use:



**PG/SG CEE/OM**

Ref. 50109/O

Inflating gun **EEC approved, for twin or spoked wheels.**  
 Pressure-gauge protecting safety valve  
 Brass inflating head, 30 cm long  
 Body: nylon  
 Lever: single operation with double acting pressure filling and release lever  
 Gauge: diam 63 mm EEC approved-range 0-10 bar  
 Length of tube: 80 cm

Operating air pressure: 1.0 - 6.0 bar  
 Package: 1 pcs  
 Weight: 590 g



**PG/S**

Ref. 50106

Inflating gun.  
 Pressure-gauge protecting safety valve  
 Body: nylon  
 Lever: single operation with double acting pressure filling and release lever  
 Gauge: diam. 63 mm double range bar/psi  
 Length of tube: 80 cm

Operating air pressure: 1.0 - 6.0 bar  
 Package: 1 pcs  
 Weight: 440 g



Recommended use:



**PG/SG**

Ref. 50107

Inflating gun, for twin or spoked wheels.  
 Pressure-gauge protecting safety valve  
 Brass inflating head, 30 cm long  
 Body: nylon  
 Lever: single operation with double acting pressure filling and release lever  
 Gauge: diam. 63 mm double range bar/psi  
 Length of tube: 80 cm

Operating air pressure: 1.0 - 6.0 bar  
 Package: 1 pcs  
 Weight: 570 g



Recommended use:



**CP**

Pressure gauge for checking pressure - double range bar/psi Ref. 50120

Pressure gauge for checking pressure - single range bar Ref. 50120/BAR

Gauge: diameter 63 mm  
 Package: 1 pcs  
 Weight: 260 g



Recommended use:



**INFLATING HEAD**

Polyamide + fibreglass version - diam. 6 mm - weight 560 g Ref. 50121

Polyamide + fibreglass version - diam. 8 mm - weight 560 g Ref. 50134

Turned brass version - diam. 6 mm - weight 660 g Ref. 50127

Turned brass version - diam. 8 mm - weight 660 g Ref. 50128

Inflating head with PRESTA valve, PRESTA HIGH, PRESTA HIGH PLUS - use: for racing bicycles - weight 685 g Ref. 50132

Package: 25 pcs



Recommended use:



**INFLATING HEAD**

Special GEM brass inflation head for paired or spoke wheels, compatible with hose diam. 6/8 mm

300 mm long version - complete with grip (\*) Ref. 50123

200 mm long version (\*\*) Ref. 50122

Package: 3 pcs  
 (\*) Weight: 460 g - (\*\*) Weight: 290 g



Recommended use:



**INFLATING KIT**

Ref. 50125

Inflation kit made up of 3 pcs.  
 Material: brass/steel  
 Use: bicycles, rafts, balls

Package: 1 pcs  
 Weight: 40 g



Recommended use:

